



NTN Bearing Rolamentos do Brasil Ltda.



63309LLU Bearing 2D drawings and 3D CAD models

45,000 mm x 100,000 mm x 39,700 mm NTN 63309LLU Deep Groove Ball Bearings

Bearing No. 63309LLU

Size	45x100x39.700 mm
Bore Diameter	45,000 mm
Outer Diameter	100,000 mm
Width	39,700 mm
d	45,000 mm
D	100,000 mm
B	39,700 mm
C	39,700 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	45MM Bore; 100MM



NTN Bearing Rolamentos do Brasil Ltda.

	Outside Diameter; 39.67MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	3
Inner Race Width	0 Inch 0 Millimeter
Bore	1.772 Inch 45 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Outer Race Width	1.562 Inch 39.67 Millimeter
bore diameter:	45 mm
precision rating:	ISO Class 0
outside diameter:	100 mm
finish/coating:	Uncoated
overall width:	39.7 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	39.70 mm



NTN Bearing Rolamentos do Brasil Ltda.

row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	39.70 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4700 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
series:	633
dynamic load capacity:	53000 N
manufacturer product page:	Click here
static load capacity:	32000 N